

SIMATIC Thin Client Ex (SIMATIC 防爆瘦客户端)

SIMATIC Thin Client Ex		订货号																		
		6AV7	2	0	0	-	0	■	■	0	0	-	■	■	A	0	-z	■	■	■
显示屏																				
防暴 2 区: 15" 带 8 个按键触屏	A																			
防暴 2 区: 19" 带 8 个按键触屏	B																			
防暴 1 区: 15" 带 8 个按键触屏	D																			
防暴 1 区: 19" 带 8 个按键触屏	E																			
防暴 1 区: 15" 触屏, 高亮显示, 带 8 个按键触屏	-																			
防暴 2 区: 15" 触屏, 阳光下可视, 带 8 个按键	G																			
防暴 1 区: 15" 触屏, 阳光下可视, 带 8 个按键	H																			
网络																				
网络 10/100 Base-Tx, Ex e	A																			
网络 100 Base-Fx LWL (SC), Ex op is	B																			
外壳选项																				
无	0																			
不锈钢外壳, 墙式安装, IP66	2																			
不锈钢外壳, 1300 mm 管状安装, 300° 可旋转, IP66	3																			
不锈钢外壳, 肘部以下 600mm 安装, 300° 可旋转, IP66	4																			
不锈钢外壳, 肘部之上 600mm 安装, 300° 可旋转, IP66	5																			
不锈钢外壳, 悬臂, 300° 可旋转	6																			
外部键盘外壳 (包括键盘外壳)																				
无键盘	A																			
键盘 QWERTZ, 安装	B																			
键盘 QWERTY, 安装	C																			
键盘 AZERTY, 安装	D																			
键盘 QWERTZ, 带轨迹球, 安装	E																			
键盘 QWERTY, 带轨迹球, 安装	F																			
键盘 AZERTY, 带轨迹球, 安装	G																			
外壳其他选项																				
通气阀 (避免凝露)	A 0 1																			
加热 (2x50W 包括温度控制器)	B 0 1																			
把手, 安装	C 0 1																			
前置 USB (安装在下侧)	D 0 1																			

最终订货号的确认及更多附件信息, 请联系西门子相关人员。